

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

THIS PAGE BLANK (USPTO)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
12 December 2002 (12.12.2002)

PCT

(10) International Publication Number
WO 02/098670 A2

- (51) International Patent Classification⁷: **B41M**
- (21) International Application Number: PCT/US02/17868
- (22) International Filing Date: 6 June 2002 (06.06.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/296,308 6 June 2001 (06.06.2001) US
60/310,914 8 August 2001 (08.08.2001) US
60/311,160 9 August 2001 (09.08.2001) US
- (71) Applicant: **SPECTRA SYSTEMS CORPORATION**
[US/US]; 321 South Main Street, Suite 102, Providence,
RI 02903 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— *without international search report and to be republished upon receipt of that report*
- (72) Inventors: **LAWANDY, Nabil, M.**; 169 Eastwick Road, North Kingstown, RI 02852 (US). **CONROY, Jeffrey, L.**; 37 Linden Avenue, Rumford, RI 02916 (US). **SMUK, Andrei, Y.**; 229 Gano Street, Providence, RI 02906 (US).
- (74) Agent: **SMITH, Harry, F.**; Harrington & Smith, LLP, 1809 Black Rock Turnpike, Fairfield, CT 06432 (US).
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: MARKING ARTICLES USING A COVERT DIGITALLY WATERMARKED IMAGE



(57) Abstract: A marking system that includes forming at least one marking in or on an article, wherein the image formed is not visible to the unaided human observer, and further contains at least one digital watermark. The digitally watermarked image comprises emissive and photoabsorptive portions. The digitally watermarked image is applied using a substance reactive to a predetermined excitation source, and exposure to ultraviolet light. Other traditional techniques, such as printing with fluorescent inks may be used in combination. The digitally watermarked image is subsequently observable upon exposure to the predetermined excitation source. The digitally watermarked image may be observed and decoded by appropriately configured detection systems, wherein the information obtained may be used for purposes including, but not limited

to, authentication and security of the article or information contained within the article.

WO 02/098670 A2

5

MARKING ARTICLES USING A COVERT DIGITALLY WATERMARKED IMAGE

FIELD OF THE INVENTION

10 This invention relates to a method and apparatus for marking and authenticating articles, such as documents, currency, credit cards, passports, product labeling and packaging and other types of objects.

BACKGROUND OF THE INVENTION

15 Valuable items such as negotiable instruments, art work, etc., are susceptible to theft and counterfeiting. With respect to documents in particular, the advancement of color copier technology has made it fairly easy to create a color copy of any document, including currency, using commonly available equipment.

20 One security device for verifying an article's authenticity is a digital watermark. Digital watermarks or similar signatures typically use semantic information associated with the protected article, such as alphanumeric characters, physical features, etc. or other related information such as ownership information. These watermarks or signatures are typically kept with or incorporated into, the item to be protected. For example, a watermark may be printed within the substrate of a negotiable instrument including information regarding the value and the originator of the instrument. As another example, digital watermarking techniques may be used for both still and video images.

30 Various digital watermarking techniques are known for both still and video images. For example, reference may be had to U.S. Patent No. 6,343,138 B1, entitled "Security Documents with Hidden Digital Data", issued January 29, 2002. This patent discloses embedding a visible digital watermark into a video signal or a still image. Another example of use of digital watermarks with documents is disclosed in U.S. Patent No. 6,243,480 B1, entitled "Digital authentication of analog documents," issued June 5, 2001.

5 There are many techniques that are used to embed additional information in a digital image. One example is disclosed in U.S. Patent No. 6,359,985, entitled a "Procedure for marking binary coded data sets," issued March 19, 2002.

10 One technique involves separately coding an image and a watermark image on an article using a pseudo random number generator and a discrete cosine transform (DCT) to term coded blocks, one of the image to be watermarked and the other of the watermark itself. The DCT coefficients representing the coded watermark block and the coded image block are then added together to form a combined block to digitally watermark the image. For example, as disclosed in U.S. Patent No. 6,037,984, entitled a "Method and Apparatus for
15 Encoding a Watermark into a Digital Image or Image Sequence," issued March 14, 2000, an image or sequence of images is watermarked using a conventional DCT unit and quantizer by generating an array of quantized DCT coefficients and watermarking the array by selecting certain DCT coefficients and replacing them with zero values. In the aforementioned patent, the array is further processed by a watermark inserter that replaces the zero valued
20 coefficients with predefined watermark coefficients, and the coefficients form a watermarked array of DCT coefficients that constitutes a watermarked image.

 Other common and known techniques for providing authentication of articles is through the use of invisible markings. One method is by printing in inks that are clear under normal illumination but emit visible fluorescent wavelengths upon ultraviolet (UV)
25 excitation. One common technique is to use invisible ink to print security marks or information.

 For documents with visible markings, it is very easy to copy or scan a document into a PC using scanning and printing technologies. In some instances, there is no way to tell if a reproduction is an original document. Even if the original document is coded with a visible
30 code, once scanned, the code could be reproduced on the counterfeit document.

 By using an invisible code or message on the document, for example "Original document – Do not copy", a scanner using visible light would not see the invisible ink. Another security feature of invisible codes recognizes that it may be difficult to reproduce the invisible ink for printing illegitimate copies. Typically, the formulation of such ink is difficult
35 to duplicate.

5 Another patent, U.S. Patent No. 6,269,169 B1, "Secure Document Reader And Method Therefor," issued July 31, 2001, discloses an apparatus and a method for reading documents.

Additional approaches to providing authentication use fluorescent markings and more sophisticated printing methods, such as printing with visible graphics. Of interest to the
10 teaching of this invention is U.S. Patent No. 6,373,965, "Apparatus And Methods For Authentication Using Partially Fluorescent Graphic Images And OCR Characters", issued April 16, 2002 discloses a system combining a source of ultraviolet light with apparatus for capturing and recognizing either graphic images or characters, or both. In this patent either a visible sub-image, or a fluorescent sub-image, or a combination image, may further contain
15 steganographic (digital watermark) information that is encoded and inserted using conventional techniques. The digital watermark information may be similarly encoded and inserted into visible and/or fluorescent sub-portions and or recombined OCR characters.

Techniques for hiding information in an invisible fashion also include the use of various frequency bands in document security design. These optical techniques exploit the
20 limitations of digital copiers and scanners by use of fine line printing patterns that use screen angle modulation of lines (SAM) and micro screen angle modulation techniques. For example, a protected document that includes background printed background matter and line pattern printed warning indicia is disclosed in United States Patent No. 4,582,346, entitled "Document Security System," issued on April 15, 1986. United States Patent No. 5,171,040,
25 entitled "Copy-Invalidating Document" issued on December 15, 1992 discloses printing a pattern of warning indicia that is merged by human sensory perception with its background, but is distinguished and reproduced by xerographic copying as a result of the employment of two different screen values for the indicia and the background within and beyond the reproductive capability of the copier machine. United States Patent No. 5,297,815, entitled
30 "Security Printed Documents" issued March 29, 1994, discloses a security document that provides an indication of when copied by a photocopy machine through the use of a background pattern and warning matter interspersed with blank areas of a substrate to provide a distinct intermeshed pattern so the warning printed is indistinguishable by the human eye. As methods of detecting and defeating security devices, such as digital watermarks, have
35 become more sophisticated, there is a growing need for advancements in markings that provide additional security.

5 SUMMARY OF THE INVENTION

Disclosed herein are methods and apparatus for covertly marking an article with a digitally watermarked image that is not visible to the unaided observer. Also disclosed is an object that carries a normally invisible digitally watermarked image.

10 An aspect of this invention involves the discreet incorporation of security information into the appearance of an object.

Another aspect of this invention is the use of substances reactive to a predetermined excitation source as a coating over an article. The coating is optically variable, that is, an
15 image formed in or with the coating appears at wavelengths outside of the visible region, and is not visible to the unaided observer.

An image that contains a digital watermark is provided on the surface of an object. The image contains a digital watermark that appears at wavelengths that are outside of the visible region of the electromagnetic spectrum. A variety of embodiments of images and digital watermarks are disclosed. Multiple watermarked images may be used for a single article, where the actual scheme selected is dependent upon, among other things, the needs of the user. The ability of an image to carry information in the form of a digital watermark provides for the discreet incorporation of information and application of security techniques.
20 The digital watermark may carry a variety of information, including information useful for as examples, the authentication of the article, and/or decryption of information related to or contained within the article.

The image and watermark may be incorporated through techniques that include printing with UV light. Combinations of coating materials and exposure techniques may be
30 used to control the appearance of the image and the digital watermark. Other methods for incorporating an image and digital watermark include traditional techniques, such as printing. Portions of the coating may be photoabsorptive. For example, portions of the coating may absorb ultraviolet light. Thus, the digital watermark may be characterized by regions that are
35 emissive, and other regions that are photoabsorptive.

5 A coating material may be used in some embodiments that is responsive to any one of a number of predetermined excitation sources, or stimuli. Possible stimuli include, but are not limited to, wavelengths of light, thermal energy, humidity, pressure, and chemical sources.

10 The image may be observed by various techniques, such as the introduction of a fluorescent background with proper illumination, or through more sophisticated means. More sophisticated means for imaging include, for example, a charge coupled device (CCD) with proper sources of illumination. The imaging device may be connected with a processor to decipher watermark information.

15 **DESCRIPTION OF THE FIGURES**

For the present invention to be understood clearly and readily practiced, the present invention will be described in conjunction with the following figures, wherein:

FIG. 1 depicts a digital watermark incorporated in a coating on an optical information
20 medium according to an embodiment of the present invention;

FIG. 2 illustrates transmission spectra of one particular lacquer at different curing times;

FIG. 3 illustrates a transmission spectra of polycarbonate substrate before and after UV
25 exposure;

FIG. 4 shows an exemplary bar code having a digital watermark;

FIG. 5 shows a schematic diagram of a detection system to identify and authenticate items in
30 accordance with an embodiment the present invention; and

FIG. 6 shows a block diagram of a detector array according to an embodiment of the present invention.

5 FIG. 7A-B, collectively referred to herein as FIG. 7, is a schematic illustration of application of coatings. FIG. 7A depicts an image printed with a reactive substance. FIG. 7B depicts an image printed with a reactive substance, with an overlay coating.

FIG. 8 is an illustration of an optical media with an information bearing marking inscribed in the
10 clamping area.

FIG. 9 is an illustration of the use of multiple digital watermarks in a credit card.

FIG. 10 is an illustration of multiple digital watermarks in registration with each other.
15

FIG. 11A-C, collectively referred to as FIG. 11, is an illustration of a split image.

DETAILED DESCRIPTION OF THE INVENTION

It is to be understood that the figures and descriptions of the present invention have been simplified to illustrate elements that are relevant for a clear understanding of the present
20 invention while eliminating, for purposes of clarity, other elements. For example, certain details relating to technologies for creating and embedding digital watermarks, such as automated or manual techniques, are not described herein. Those of ordinary skill in the art will recognize, however, that these and other elements may be desirable in a typical digital watermarking algorithm. A discussion of such elements is not provided because such
25 elements are well known in the art and because they do not facilitate a better understanding of the present invention.

Disclosed herein are methods and apparatus for incorporating an image (also referred to herein as a "marking" or as a "mark") containing a digital watermark (also referred to
30 herein as a "watermark") into or onto an article, where the marking and the watermark are only partially visible to an unaided observer, or they are invisible to the unaided observer. As referred to herein, it is generally considered that "visible" images and marks appear at wavelengths between about 400 nm to about 700nm. "Invisible" images and marks may appear at wavelengths above the visible spectrum (above about 700 nm), which is herein
35 referred to for purposes herein the infrared region, or IR; or, invisible images and marks may appear at wavelengths below the visible spectrum (downward from about 400 nm), in what is

5 referred to herein the ultraviolet region, or UV. "Normally invisible," as used herein, refers to the visibility of a marking without the introduction of an external stimulus. Thus, it can be appreciated that an invisible image that becomes visible only upon exposure to a stimulus, for example, UV light, is "normally invisible." Additionally, invisible markings may appear at various wavelengths simultaneously.

10

The "unaided observer" may be a human and/or a detection system. A degree of authentication may occur by the human observer, where the human observer is possessed by the ability to verify the presence of an image, and may be able to verify certain characteristics related to the image. Detection systems have improved capabilities over a human observer, and may detect additional features of a mark, such as the presence and content of a digital watermark. Typically, a human observer is not able to detect a digital watermark, and additionally, the human observer will not be able to decipher a digital watermark without the aid of a detection system. However, the covert nature of the markings disclosed herein require that a detection system be "appropriately configured" in order to detect and decipher the marking. For example, characteristics of an "appropriately configured" detection system include, but are not limited to, illumination at proper wavelengths, and possession of digital watermarking algorithm information in order to decipher a digital watermark.

Invisible images may be observed through use of various intermediate mechanisms. For example, UV absorptive markings may be observed through the introduction of fluorescent materials that are emissive in the visible region. As an alternate example, an image may be observed in the IR region through use of equipment, such as a charge coupled device, appropriately configured to detect IR wavelengths. One skilled in the art will realize that many embodiments are possible, where images that are not visible to the unaided observer may viewed in the visible region, or through use of appropriately configured detection equipment presenting a visible portrayal of the image.

The image may include various conventions for presentation of data, including, but not limited to, data code symbologies, such as a bar code, graphics, text, alphanumeric, and digital watermarks.

The present invention relates to a method for processing an article to embed auxiliary data and the subsequent extraction and use of such data. In accordance with embodiments

5 described herein, an image containing a multi-bit marking may be embedded directly or printed on the article, such as a security document, an optical storage media, or other article. Hardware or software systems can then read the marking, for example, to identify and authenticate the subject article.

10 The watermark is encoded within the image, and becomes part of the image. The watermark preferably cannot be detected or removed without prior knowledge of the specifics of the watermark. While the changes manifested by the incorporation of the watermark are generally too slight to be visible to the human eye, when a marked image appears, they are easily and consistently recognizable by, for example, a digital image scanner or a charge-
15 coupled device where after recognition and imaging the marking is extracted interpreted and verified by, for example, a software algorithm.

The Marking

One non-limiting embodiment of the teachings herein describe use of a coating for application to an article, for example, an optical information medium such as a CD-ROM
20 (compact disc, read-only-memory) or DVD (digital versatile disc). FIG. 1 shows an exemplary article 420, such as an optical information media, that includes a coating 450 that is supportive of an image 432, also referred to herein as a "marking." The marking 432 contains a digital watermark 435.

25 In accordance with the invention, the marking 432 is invisible, or substantially invisible, to the unaided observer. The coating 450 may have absorption properties such that it does not absorb a "readout" wavelength or wavelengths, such as those wavelengths used to read a CD-ROM or a DVD. The coating is applied in a manner that is consistent with the teachings herein, and the image and mark are likewise subsequently applied to the coating in
30 a manner consistent with the teachings herein.

While the teachings herein are frequently described in the context of an optical information medium such as a CD-ROM or a DVD, the use of these articles is considered to be illustrative and is not limiting of the invention. It should be understood that the invention
35 includes any article suitable for receiving a coating in accordance with these teachings. For example, the invention may be used to provide for marking of securities, product packages,

5 labels, notes of currency, identification, credit cards, diplomas, passports, licenses, windshields, documents, and other items.

In another embodiment, a marking 432 and a digital watermark 435 are formed through deposition of a coating 450. In this embodiment, the coating 450 may be formed of,
10 for example, a fluorescent ink.

Marking 432 may include, e.g., text information, such as a word or words, graphic information, such as a logo or barcode, or any other suitable information. According to a preferred embodiment, marking 432 includes embedded information (also called "coding information") and / or authentication signatures included in the digital watermark 435. For
15 example, a digital watermark 435 may contain distribution chain or manufacturer specific information, the date of manufacture, the country of origin, the authorized distribution channel, or any other information that may be informative or useful about the article. It also might contain a hash value of the semantic information printed on the article for use in
20 comparison for forgery detection. Thus, the article 420 may also carry additional information in a digital watermark 435 that may not be discernable without knowledge of digital watermark 435 and the ability to read the information included therein. Such indiscernible information may be useful for various applications, for instance with respect to the anti-diversion of branded products.

25 According to another embodiment, coding information for a digital watermark 435 may be generated from one or more physical characteristics or attributes of article 420. The coding information may be used as an input to the digital watermark 435. For example, the coding information may include attributes of the information recorded on article 420 such as
30 the number of recorded titles, the author, the playtime of the CD or DVD, copyright dates, a serial number, an indication of the content owner, etc. Such physical characteristics may be directly or indirectly observable. For example, the characteristics included in the digital watermark 435 preferably require processing by a suitably programmed digital data processor with appropriate sensors, detectors, illumination sources, etc. in order to be detected and
35 decoded.

The digital watermark 435 may be created using any of a number of methods. One example of a method for creating digital watermark 435 may include using the coding

5 information as a seed or a pseudo-random number generator where the random number is used as a hash or some other one-way function for generating digital watermark 435. Another technique may include using the coding information, the output of a pseudo-random number generator, and any other appropriate information as distinct inputs to an algorithm including a discrete cosine transform to form a digitally watermarked image. In another
10 embodiment, one or more of the various inputs to the digital watermarking algorithm may be used as a key to "unlock" or otherwise obtain information included in digital watermark 435, or other information, such as information within the article 420.

By whatever means created, and as was noted above, the digitally watermarked image
15 or marking 432 is invisible or substantially invisible to the unaided observer.

The Coating

The coating 450 is formed of a substance that is reactive to a predetermined excitation source. A variety of materials may be used; the actual material selected depends upon, among other things, the needs of the user regarding a particular application. Examples of
20 excitation sources, include, but are not limited to, illumination with electromagnetic radiation, including certain wavelengths of light; chemical; thermal; pressure; and, humidity. Once applied, the coating 450 does not significantly interfere with the use or functionality of the article 420. For example, in the case of optical media 420, the coating 450 does not interfere with the readout laser mechanism, and the recovery of data from the optical media
25 420.

Techniques for applying coating 450 may include, but are not limited to, printing, spraying, rolling, silk-screening, painting, or any other technique suitable for applying the coating 450 as described herein. Coating 450 may be processed or applied in a manner to
30 exhibit the marking 432 and the digital watermark 435. According to an embodiment, the coating 450 can be printed, photo-bleached with a mask, engraved and / or ablated to exhibit the marking 432. According to another embodiment, the coating 450 may be processed to exhibit the marking 432 by directly writing with a laser or any other suitable laser writing technique.

35

Coating 450 may be colored or colorless to the eye, and may be fluorescent under certain electromagnetic radiation. According to an embodiment, coating 450 includes

5 compounds such as metal chelates, fluorescent dyes or laser dyes. According to other
embodiments, coating 450 includes organic phosphors or inorganic phosphors. For example,
coating 450 may include an inorganic phosphor such as silver doped zinc sulfide (Ag:ZnS).
According to another embodiment in which coating 450 is fluorescent, coating 450 may
include a thermoplastic resin and an insoluble fluorescent pigment in a suitable carrier.
10 According to a further embodiment, the pigment may include a dye dissolved in a plastic
material.

According to an embodiment, the coating 450 may be applied to an optical
information medium 420 (for example, the play side). In this embodiment, readout light
15 wavelengths for the optical information medium 420 may include wavelengths of about
400nm, about 440nm, about 630nm, about 650nm, about 780nm, or any other readout
wavelength, or combination of wavelengths, that may be employed to read information from
optical information medium 420. Those of ordinary skill in the art will appreciate that
coating 450 may be applied to either the "play" or "non-play" side of optical information
20 medium 420. In this embodiment, the coating 450 may have any desired thickness, provided
the thickness does not interfere with the readout of optical information medium 420 when
applied to the readout side of medium 420. The coating 450 may be observable at any
wavelength, other than wavelengths that would be substantially interfering with the readout
mechanism of the optical information medium 420.

25

According to embodiments where the coating 450 is fluorescent, the coating 450 may
absorb electromagnetic radiation either at ultraviolet (UV), visible, near infrared (IR), or
longer wavelengths. The fluorescent coating 450 may emit wavelengths in any one of UV,
near UV, near IR or IR regions. According to another embodiment, where the coating 450 is
30 a colorless fluorescent coating 450, the marking 432 may only appear under illumination with
a predetermined source, such as a UV light source.

Printing with UV Light

35 The disclosed technique of invisible, or substantially invisible, printing by UV light is
based on several mechanisms. One mechanism recognizes the property of some materials to
become more absorbing of UV light due to progressive exposure of the material to UV light.
This property is exhibited by a number of polymers and glasses, and is attributed to

5 photogeneration of defects that contribute to the absorption in the UV region of the electromagnetic spectrum (called the "defect generation mechanism"). FIG. 2 illustrates the effect of this mechanism, showing the transmission spectra of a polycarbonate substrate before and after exposure to intense UV light produced by Xenon RC-747TM pulsed lamp.

10 In addition to the defect generation mechanism, another mechanism is possible, such as in the case of photocurable polymers. As UV light leads to polymerization of a monomeric coating, the total UV exposure will determine the degree of polymerization of the material, and therefore, its optical properties including UV absorption in particular. Thus, exposure of a partially cured film to UV light results in higher degree of polymerization,
15 which accounts for the difference in UV absorption compared to the original less-cured material (called the "curing time mechanism"). FIG. 3 illustrates the effect of this mechanism, showing the transmission spectra of a 19- μ m-thick layer of Sony Chemicals lacquer SK6400 cured by UV light of a Xenon RC-747TM pulsed lamp with total exposure times of three seconds and one minute.

20

Due to either of the aforementioned mechanisms, selective UV exposure of some areas of certain substrates result in the formation of latent contrast between the exposed and virgin parts of the substrate. In one embodiment, this contrast becomes visible by placing a fluorescent layer under the substrate and illuminating a polymeric substrate with longwave
25 UV or "black" light. Higher absorption of the illumination by the previously exposed areas of the substrate results in lower excitation levels of the underlying fluorescent layer and, consequently, lower brightness of the fluorescence, thereby producing a visible contrast. The substrate is assumed to be at least partially transmissive to the UV excitation and fluorescent emission.

30

Latent contrast formation is also possible using a further mechanism, called photobleaching that induces modification of the optical properties of a target molecule by irradiation of the target with UV. This technique may be practiced in a host polymer, provided the host is supportive of irradiation with UV. In one embodiment, a UV sensitive
35 fluorescent additive is used as a target molecule, where the additive is mixed into a UV transparent polymer. In this embodiment, irradiation of the substrate with UV provides for modification of the optical properties of the fluorescent additive.

5 Latent contrast may be achieved by using the three methods alone, or in combination. For example, fluorescent pigment may be intermixed with a coating 450 that carries the invisible print according to an embodiment of the present invention. This technique can be used for making invisible markings 432 on the read out surfaces of optical discs such as CDs and DVDs. A clear polymer impregnated with a fluorescent additive is applied to the read
10 out surface of an optical disc 420 by spin-coating and, subsequently, is cured. According to such an embodiment, coating 450 is uniform and transparent in the visible and near-IR regions of the spectrum and, therefore, produces no interference with the read out laser beam. At this point in the manufacturing process, the coating 450 produces uniform fluorescence across the entire coated area. A desired marking 432 may be transferred onto the coating 450
15 by the above mechanisms of photoinduced UV absorption, and / or by photobleaching. The transfer may be achieved through UV irradiation using, for example, a photomask or by a direct laser writing process.

Any of the above-mentioned mechanisms may be used to fabricate an image 432
20 containing a watermark 435. For example, a gray-scale image 432 encoded with a watermark 435 is printed on a UV-transparent substrate, with gray-scale print providing spatially variable attenuation for the UV radiation in accordance with the desired watermarked image 432, thereby providing a photomask for subsequent transfer of the contrast onto a fluorescent polymeric substrate 420. Exposure of the fluorescent polymer to an intense UV-source
25 through the prepared photomask results in transfer of the watermarked image 432 onto the fluorescent polymer as a latent contrast. This latent contrast can be visualized, for example, via fluorescence under low-intensity UV radiation or "black" light and the watermarked image 432 read out and decoded. Since digital watermarking supports inversion of contrast, either a positive or a negative photomask can be used, with the final fluorescent contrast
30 being respectively negative or positive, while preserving the encoded watermark 435. An example of a system that is supportive of this technique is the SysCop™ system available from MediaSec Technologies of Providence, Rhode Island.

FIG. 7 depicts embodiments of markings 432 with digital watermarks 435. In FIG. 7A,
35 a marking 432 with a digital watermark 435 is printed onto a substrate using a substance that is reactive to an excitation source. FIG. 7A depicts a marking 432 that is visible when illuminated with wavelengths of UV light. For convenience, the area of the marking over the article 420 is identified from the article 420 side of the marking 432. The coating 450 absorbs light in the UV

5 region, thereby causing a fluorescent emission in the visible region. FIG. 7B depicts another embodiment, where the embodiment shown in FIG. 7A is further embellished with another coating 450A, where a portion 450A-1 of the coating 450A has been irradiated with UV light. In FIG. 7B, the portion of the second coating 450A-1 provides photoabsorption of wavelengths of UV light, thereby providing a perception of an image 432 that is modified from the image 432
10 that appears in FIG. 7A.

FIG. 8 is an illustration of an embodiment where information has been transferred onto an optical media 420. In FIG. 8, the optical media 420 is a CD or DVD, which has a central clamping area 422 that is not used for the storage of data. The central clamping area 422 is
15 substantially transparent. In this embodiment, an image 432 includes a watermark 435, which is formed in the clamping area 422 through use of a photomask, or any other suitable technique. The marking 432 was previously transferred in a predetermined pattern according to the needs of the user. In this embodiment, viewing of the image 432 and the mark 435 involves placing the optical media 420 over a fluorescent background 414. The fluorescent background 414 is
20 independent of the optical media 420, and is supplied to provide contrast when exposed to UV light. UV light may be supplied by a low intensity UV light supply 415. Once the optical media 420 is placed over the fluorescent background 414 and exposed to UV light from the UV light supply 415, the latent contrast from the UV exposure becomes apparent and the information bearing marking 432 becomes visible.

25

According to another embodiment of the present invention, a fluorescent polymeric layer is applied between the halves of a DVD 420. The latent image 432 is produced on the read out side (also called the "label side") by selective exposure of the DVD 420 to intense UV light through a photomask or by direct writing with a UV laser. Subsequent "black" light
30 illumination generates a visible contrast fluorescence pattern. In this embodiment, the fluorescent layer is attached to the substrate 420 that is carrying the invisible print.

Latent contrast may be used alone or in combination with other techniques to create or enhance a digital watermark 435. In the embodiments where latent contrast is included in the
35 digital watermark 435, the digital watermark 435 is characterized by portions that are at least partially absorptive of UV. Examples include, but are not limited to, embodiments such as the embodiment depicted in FIG. 7B; and other embodiments where exposure to UV may be used to create shading and / or other effects. Further embodiments make use of

5 photobleaching, where the fluorescent dye used in an invisible watermark is modified. In these embodiments, a UV laser may be used to enhance the marking, and provide for degrees of detail or control that may not be achievable through traditional techniques for application of fluorescent ink.

10 It may therefore be realized by one of ordinary skill in the art, that the cooperation of ultraviolet irradiation and other techniques can provide for a degree of refinement in invisible images not otherwise attainable.

Detection

15 A detector in combination with an excitation source may be used to read or display the coating 450. The detector-source combination may be, for example, a handheld reader with a self contained UV source, such as a xenon flash source. The reader may also include a CCD pixel array and a display. One suitable type of detector is known as VeriCam™, available from Spectra Systems of Providence, Rhode Island. According to another
20 embodiment, the reader may include a visible light scanner to convert the image to a digitized form.

In another embodiment, a bar code symbology may be impregnated with a digital watermark 435. FIG. 4 shows an example of such a bar code 432. Barcode 432 may be
25 implemented using any suitable symbology including, without limitation, 3 of 9, 12 of 5, Code 128, UPC, 2-D, and 3-D symbologies. In addition to being encrypted with digitally watermarked information, bar code 432 can be made to contain a pass key to allow reading of bar code 432 itself. If the digital watermark 435 is not read, a properly designed terminal will not read bar code 432. The watermark 435 may be incorporated, for example, as a digitally
30 embedded imprint in the bit pattern or noise of a digital image of the bar code 432.

Software technologies may be used to embed the digital watermark 435 such that it is recoverable using software or other automated or manual techniques. The digital watermark 435 may also include additional information that may be decoded by using a key to “unlock”
35 data, for example, data included in another digital watermark 435, or data within the article 420. The digital watermark 435, and the other information that may be embedded in the digital watermark 435, is robust to image deformations, rotations, copying, multiple renderings, conversions, and other manipulations.

5

With respect to FIG. 1, the decoding or identification of coating 450 may employ imaging of the coating 450 and/or the unique marking 432 as well as the detection of fluorescent emission or color if present. This can be achieved, for example, by using a microscope system coupled to a monolithic spectrometer.

10

Another embodiment may use a narrow band filtered detection system including CCD camera-based devices. Use of these, and other appropriately configured detection systems may provide for observation of markings 432 that are not otherwise visible to the unaided observer. Such systems may be used, among other things, to detect an image 432, and to present a copy of the image 432 to a user, wherein the copy is provided by a device presenting the image 432 in the visible region. For example, an image 432 that appears in the ultraviolet or the infrared region may be viewed using appropriate equipment that includes a detector configured to detect in the appropriate region, connected with image processing equipment and a display monitor, wherein the display monitor provides for viewing of the image 432 by the human observer. However, the slight variations in the image 432 that compose the digital watermark 435 may, or may not, become apparent. In this manner, as one example, images 432 that were otherwise undetectable to a human observer become observable.

25

FIG. 5 shows an exemplary detection system 400 according to an embodiment of the present invention. A source of radiation 410 is directed on article 420 to be examined, such as a CD-ROM, DVD, or other suitable type of optically encoded medium. Source 410 may generate any type of radiation, such as UV radiation, that is suitable for detecting coating 450 included on article 420 and/or watermark 435 or any appropriate attributes of article 420. Article 420 may be mounted on a positioning device 425 to locate article 420 for irradiation. Positioning device 425 may include a conveyor or any other type of device suitable for transporting or locating the article 420 for irradiation. Detection system 400 may also include a detector array 430, such as a CCD camera or other suitable detection device with appropriate support circuitry 440 for detecting an image of article 420 and watermark 435. Detector array 430 may be fixed, moveable or handheld. Source 410 and detector array 430 may also comprise positioning devices (not shown) for locating these devices for optimum performance. Detector array 430 may be capable of detecting the spectral content of any emissions, in addition to any other physical characteristics of watermark 435 or article 420

35

5 for identification and authentication of article 420. Control circuitry 460 directs the activity of system 400, and in particular controls source 410, positioning device 425, detector array 436 and support circuitry 440. It is also within the scope or the invention to use a simple handheld reader, such as the one described above, as a detection system 400.

10 According to an embodiment shown in FIG. 6, a detector array 430 includes an optical section 470 for focusing received emissions within detector array 430, an array of sensors 480 for detecting the emissions, and a filter section 490 for allowing only the frequencies of interest to impinge on sensors 480. Optical section 470 may include a microscope system or any other system suitable for magnifying or otherwise focusing the
15 image of article 420 and/or any emissions from item 420 within the detector array 430. The sensor array 480 may include any array of sensors suitable for detecting the emissions and/or physical characteristics of article 420 such as, for example, a diode array, a CCD array, etc. The sensor array 480 may be a one dimensional linear array that is scanned relative to the marking 432, or it may be a two dimensional area array that provides for "snap shot".
20 imaging. Using this arrangement, the output of the detector array 430 is analyzed to detect the characteristics of and thereby interpret watermark 435 and/or coating 450 so as to identify and authenticate article 420, such as by obtaining plural bit data contained in the digital watermark 435.

25 Further Embodiments

A variety of embodiments of the invention disclosed herein is possible. One skilled in the art will recognize that the embodiments disclosed herein are illustrative of features of this invention, and are not limiting of the invention. One skilled in the art will also recognize that
30 many variations of this invention are achievable without deviation from the spirit of this invention. Among other things, the needs of the user play a role in the determination of the actual scheme used. Examples of further embodiments are thus now provided.

Multiple images 432 containing watermarks 435 may be used to mark a single article
35 420. Images 432 may be disposed upon the article 420 with a distinct relationship to each other. For example, an image 432 could be overlapping, concentric, in registration with, or offset by some predetermined value from, another image 432. The positioning of images 432 relative to each other, or on an article 420, may be used to provide additional information to a

5 user. In another example, a first image 432 and watermark 435 may be not be apparent at visible wavelengths, while a second image 432 and watermark 435 may appear at visible wavelengths.

10 Images 432 may be used in cooperation with one another. For example, the first image 432, once detected may be used to locate the second image 432. FIGS. 11A-11C depict an example of a "split" image 432. FIG. 11A depicts one compliment 432L of the image 432, which may be referred to for convenience as a "left handed" portion. FIG 11B depicts the right handed compliment 432R of the image 432. FIG. 11C depicts the image 432, after a processor has assembled the left and right images 432. A "split" image 432 may
15 be used, which contains a portion of a total image 432 and/or watermark 435, where the complimentary portion is contained in a complimentary image 432, or multiples of images 432. The split image 432 may be reconstructed into a single image 432, among other means, by use of a processing system that is appropriately configured.

20 In other embodiments, the information contained in a digital watermark 435 is used in some relationship to other digital watermarks 435 incorporated with the article 420. For example, one digital watermark 435 may be used as a key to another digital watermark 435. FIG 9. provides an example of this embodiment.

25 In the embodiment shown in FIG. 9, a first image 432 and digital watermark 435A is not visible to a human observer under normal illumination with visible wavelengths. Information contained in the watermark 435A may be used for an authentication of a bank card 420, where the presence of the watermark 435A, or information contained within the watermark 435A, is compared to corresponding features of an authentic version of the mark
30 435A. Once authenticated, the detection and authentication system that is used to detect the mark is directed to a second invisible image 432 and digital watermark 435B. In this embodiment, the second watermark 435B may carry additional information, such as a decryption key used to gain access to a bank card system. In another embodiment, a first digital watermark 435A may be observed by detection systems using visible light to excite
35 the materials, which thereby causes the substrate materials to fluoresce in the IR region. In this embodiment, the second digital watermark 435B may be observed by detection systems using non-visible light, such as ultraviolet light.

5 In one variation of this embodiment, the second digital watermark 435B is formed of
a material that may be imaged at a predetermined IR wavelength. A component of the
detection system is configured to detect a narrow band of IR wavelengths containing the
predetermined wavelength. In this example, the second watermark 435B may contain
information needed by the user, such as, for example, encoded biometric data for verification
10 of identity.

As shown in FIG 10, another embodiment involves use of digital watermarks 435 in
registration with each other. For example, a visible digital watermark 435A is applied to an
article 420, with a second and invisible digital watermark 435B applied in registration with
15 the first digital watermark 435A. As an alternate embodiment, the first digital watermark
435A and the second digital watermark 435B may be included in concentric images with
varied appearance. In these embodiments, the first digital watermark 435A may appear when
illuminated by a predetermined first band of wavelengths, for example in the UV region, and
the second digital watermark 435B may appear when illuminated by a predetermined second
20 band of wavelengths, for example in the IR region.

It is easily recognizable by one of ordinary skill in the art that many embodiments
may be realized. For example, one may vary aspects such as, but not limited to, the
wavelength at which a watermark 435 may appear, the number of watermarks 435 in use,
25 placement of watermarks 435, the information contained in a watermark 435, and the use of
watermarks 435 as sources of various information, such as keys for access to other
information.

In some embodiments of these teachings other stimuli may be used to make a
30 normally invisible marking 432 become visible, such as but not limited to, at least one of the
application of heat, a change in humidity, a change in pressure, or the application of one or
more chemical agents.

Preferably, after the stimulus is removed, the marking 432 one more becomes
35 invisible, or substantially invisible, to the unaided observer, the observer being either a
human or machine observer.

- 5 It can thus be appreciated that while the invention has been particularly shown and described with respect to preferred embodiments thereof, it will be understood by those skilled in the art that changes in form and details may be made therein without departing from the scope and spirit of the invention.

WHAT IS CLAIMED IS:

1. An object comprising at least one digitally watermarked image, said digitally watermarked image being normally invisible and comprising a material that causes said digitally watermarked image to become detectable due at least in part to an optically absorptive property of said digitally watermarked image when exposed to a predetermined excitation source.
2. The object as in claim 1, wherein said digitally watermarked image includes a data code symbology comprising at least one of a bar code, a graphic, text, and alphanumeric characters.
3. The object as in claim 1, wherein said digitally watermarked image comprising at least one digital watermark is disposed upon said article in a coating.
4. The object as in claim 3, wherein said coating comprises at least one of a polymeric material, a monomeric material, a metal chelate, an organic phosphor, an inorganic phosphor, a fluorescent dye and a laser dye.
5. The object as in claim 1, wherein said digitally watermarked image comprises information for purposes comprising at least one of authentication of said article, providing a relationship to said article, providing access to a digital watermark, providing access to said article, providing access to information contained within said article, and providing a key for decrypting encrypted information.
6. The object as in claim 1, wherein said digitally watermarked image comprises a decryption key.
7. The object as in claim 1, wherein said object comprises one of an optical media, a security document, a note of currency, a product package, a label, an identification, and a credit card.

8. An article comprising a marking, the marking comprising:
 - a first digitally watermarked image, said digitally watermarked image being normally invisible and comprising a material that causes said digitally watermarked image to become detectable due at least in part to an optically absorptive property of said digitally watermarked image when exposed to a predetermined excitation source; and,
 - a second digitally watermarked image disposed upon said article, wherein said second digitally watermarked image is substantially observable to the unaided observer.
9. An article as in claim 8, wherein said first digitally watermarked image is in registration with said second digitally watermarked image.
10. An article as in claim 8, wherein said first digitally watermarked image is offset from said second digitally watermarked image.
11. An article as in claim 8, wherein said first digitally watermarked image is concentric with said second digitally watermarked image.
12. An article as in claim 8, wherein said first digitally watermarked image and said second digitally watermarked image each comprise at least a complimentary portion of a complete digitally watermarked image of said marking.
13. An article as in claim 8, wherein at least one of said digitally watermarked images comprises information for purposes comprising at least one of authentication of said article, providing a relationship to said article, providing access to a digital watermark, providing access to said article, providing access to information contained within said article, and providing a key for decrypting encrypted information.
14. An article as in claim 8, wherein at least one of said watermarks comprises a decryption key.

15. An article comprising a marking, the marking comprising:
 - a first digitally watermarked image, said digitally watermarked image being normally invisible and comprising a material that causes said digitally watermarked image to become detectable due at least in part to an optically absorptive property of said digitally watermarked image when exposed to a first predetermined excitation source; and,
 - at least one second digitally watermarked image, said second digitally watermarked image being normally invisible and comprising a material that causes said second digitally watermarked image to become detectable when exposed to a second predetermined excitation source.
16. An article as in claim 15, wherein said first digitally watermarked image is in registration with said at least one second digitally watermarked image.
17. An article as in claim 15, wherein said first digitally watermarked image is offset from said at least one second digitally watermarked image.
18. An article as in claim 15, wherein said first digitally watermarked image is concentric with said at least one second digitally watermarked image.
19. An article as in claim 15, wherein said first digitally watermarked image is overlapping with said at least one second digitally watermarked image.
20. An article as in claim 15, wherein at least one of said digitally watermarked images comprises information for purposes comprising at least one of authentication of said article, providing a relationship to said article, providing access to a digital watermark, providing access to said article, providing access to information contained within said article, and providing a key for decrypting encrypted information.
21. An article as in claim 15, wherein said first predetermined excitation source and said second predetermined excitation source comprise one of a same excitation source or two excitation sources.

22. A method of forming a mark on an article, comprising:
selecting a marking for said article; and,
exposing said article to ultraviolet light for applying at least one digitally watermarked image of said marking to said article, wherein said at least one digitally watermarked image is not substantially observable to the unaided observer, and said at least one digitally watermarked image being observable upon exposure to a predetermined excitation source.
23. A method as in claim 22, wherein exposing is preceded by applying a coating to said article.
24. A method as in claim 23, wherein said coating comprises at least one of a polymeric material, a monomeric material, a metal chelate, an organic phosphor, an inorganic phosphor, a fluorescent dye and a laser dye.
25. A method as in claim 22, wherein applying comprises at least one of printing, spraying, rolling, silk screening and painting.
26. A method as in claim 22, wherein applying comprises use of at least one of a positive photomask, a negative photomask, and a UV laser.
27. A method as in claim 22, wherein applying comprises applying a portion of said mark in a first image, and at least one complimentary portion of said mark in at least one second image.

28. A method of examining an article containing a mark, the method comprising:
- providing an article having said mark, said mark comprising at least one digitally watermarked image, said digitally watermarked image being normally invisible and comprising a material that causes said digitally watermarked image to become detectable due at least in part to an optically absorptive property of said digitally watermarked image when exposed to a predetermined excitation source;
 - exposing said article to said predetermined excitation source;
 - detecting said at least one digital watermark in accordance with at least a partial absorption of UV light; and,
 - decoding said at least one digital watermark.
29. The method as in claim 28, wherein said predetermined excitation source comprises at least one of a source of certain wavelengths of electromagnetic radiation, a source of a chemical agent, a source of thermal energy, a source of pressure, and source of humidity.
30. The method as in claim 28, wherein said predetermined excitation source comprises at least one of ultraviolet light, visible light, and infrared light.
31. The method according to claim 28, wherein detecting comprises using at least one of a charge coupled device and a visible light scanner.
32. The method according to claim 28, wherein detecting comprises using a hand held device comprising a detector and said predetermined excitation source.
33. The method according to claim 28, wherein detecting comprises at least one of an array of ultraviolet light sensors and an array of infrared light sensors.
34. The method according to claim 28, further comprising:
- comparing at least one said digital watermark to predetermined authentication information for said article; and
 - verifying authenticity of said article based upon the comparison.

35. The method as in claim 34, further comprising, when said article's authenticity has been verified, enabling access to information contained in said article.
36. The method according to claim 28, further comprising:
 - using information from said at least one digital watermark to decrypt further information, wherein said further information is included in at least one of another mark and said article.
37. The method according to claim 28, wherein said at least one digitally watermarked image comprises a first complimentary digitally watermarked image and a second complimentary digitally watermarked image, the method further comprising:
 - forming a complete digitally watermarked image from a combination of said first complimentary digitally watermarked image and said second complimentary digitally watermarked image.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C

